THE BEST & LAST ROOF COATING YOU'LL EVER USE!

SINCE 195

WARRANT

A GRCO

nn

Gaco



STANDARD COLORS

WHITE

Metal	Sprayed Polyurethane Foam
Tar & Gravel	Low-Pitched Roofs
Cap Sheet	Flat Roofs
Torchdown	Mobile Homes
Composite	RVs & Campers
Aged Asphalt	Built-Up Roofs
Modified Bitumen	EPDM & Aged TPO*
Barrel Tile	*Surface may require primer

GRAY

GACO

GREEN

(FLIP OVER) TO COMPARE

WWW.GACORETAIL.COM (866) 422-6489

INITED FIF

g

GACO

COMPARE FOR YOURSELF:



	GACOROOF	Brand X
Warranty	LIMITED 50-YEAR	5-10 Years
Can be applied between 32° - 120°	YES	NO
Withstands Permanent Ponding Water	YES	NO
Primer/ Basecoat Required?	N 🗆 *	YES
Recoating Required?	ND	YES

- 2 coat application of same product Brand X requires multiple products
- Withstands permanent ponding water Brand X is 48 hours only
- Temperature application range 32°-120° F
 Brand X is 50°-90° F
- **1-12 hour cure time, dry to the touch** *Brand X is 24-48 hours*
- **1** gallon = 100 sq. ft. per coat Brand X is 1.5 gallons
- Can be used on "Flat Roofs" Brand X requires 1/4" slope
- Can be rained on after 2 hours Brand X requires no "rain, dew or fog within 24-48 hours
- **Permanently flexible** Brand X becomes brittle and begins to degrade over time

- Recoat can be done after cure time Brand X may require 24 hours before recoat
- Silicone Roof Coating Brand X all sell acrylic roof coatings
- Ponding WaterProof Brand X is ponding water Resistant
- **50 year warranty** Brand X 5-10 years
- No polyester mat between coats Brand X requires
- UV resistant Brand X loses mil thickness due to UV exposure
- 22 mil system Brand X is 48-60 mil

*EPDM & Aged TPO may require primer. Use a GacoRoof Adhesion Test Kit to test for proper adhesion.

